

# DA-77



## Specification

Thermal efficiency	
U <sub>w</sub> *: Coefficient value for reference design	1,0 W/m <sup>2</sup> K
U factor*:	0,18 Btu/h·ft <sup>2</sup> ·F
*:	Glass 4/18/4/18/4 window size 48 7/16 in x 58 4/16 in (1230 mm x 1480 mm)
Profile	
Profile name:	DA-77
Installation depth:	Frame 77 mm   Sash 86 mm
Number of chambers:	4
Thermal break:	yes: 43 mm
Number of seals:	2
Glass	
Glazing package:	4/18/4/18/4 warm spacer bar
U <sub>g</sub> value:	0,5 W/m <sup>2</sup> K
Glazing Package Thickness:	from 21 to 67 mm
Sound insulation of available glazing:	---
Fittings	

Type:	Winkhaus circumferential
Hinges:	surface
Anti-theft protection:	anti-theft catches
Microventilation:	yes
Other:	Four-stage tilt and slide mechanism   Handle rotation lock with a lifter
<b>Handle</b>	
Colors:	---
Handle model:	1006
<b>Dimensions</b>	
Maximum window width - single sash:	1700 mm
Maximum window height - single sash:	2800 mm
Maximum window width - double sash with a movable post:	3400 mm
Maximum window height - double sash with a movable post:	2800 mm
Maximum sash area:	3 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg):	3500 x 2900 mm lub 2900 x 3500 mm

## Photos

