

# DDA-78



## Specification

| Thermal efficiency  |   |
|---|---|
| U <sub>w</sub> *:<br>Coefficient value for reference design | 0,85 W/m <sup>2</sup> K   |
| U factor*:  | 0,13* Btu/h·ft <sup>2</sup> ·F  |
| *:  | Glass: 4/16/4/16/4; gas: argon; warm edge spacer;<br>window size: 48 7/16in x 58 4/16in (1230 mm x 1480 mm) |
| Profile   |   |
| Profile name:   | DDA-78  |
| Installation depth:   | 95 mm   |
| Number of chambers:   | n/a   |
| Thermal break:  | n/a   |
| Number of seals:  | 3   |
| Glass   |   |
| Glazing package:  | 4/14/4/14/4   |
| U <sub>g</sub> value:                                       | 0,6 W/m <sup>2</sup> K  |
| Glazing Package Thickness:                                  | 40 mm   |
| Sound insulation of available glazing:                      | ---   |
| Fittings  |   |

|   |                                   |
|---|-----------------------------------|
| Type:   | ---                               |
| Hinges:   | surface                           |
| Anti-theft protection:  | 1 anti-theft catch                |
| Microventilation:   | yes                               |
| Other:  | ---                               |
| <b>Handle</b>   |                                   |
| Colors:   | ---                               |
| Handle model:   | 1006                              |
| <b>Dimensions</b>   |                                   |
| Maximum window width - single sash:   | 1500 mm                           |
| Maximum window height - single sash:  | 2525 mm                           |
| Maximum window width - double sash with a movable post:   | 2080 mm                           |
| Maximum window height - double sash with a movable post:  | 2525 mm                           |
| Maximum sash area:  | 3 m <sup>2</sup>                  |
| Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg): | 3500 x 2900 mm lub 2900 x 3500 mm |

## Photos

